

CHECK OUT YOUR OIL &

(SWEPT 306) = 6000
15W-50 MOBIL ZDDP MUST BE ABOVE 1200 PPM

Mobil 1 Engine Oils

Additional product information, including Product Data Sheets and this chart, is available at MobilOil.com

Brand	Viscosity	Nominal Phosphorus Level, PPM	Nominal Zinc Level, PPM	Product Description	Recommended Consumer Applications	API, ILSAC, and Other Industry Approvals***	ACEA Approvals	GM Service Fill Approval	Ford Service Fill Approval	Chrysler Service Fill Approval	MB Approval	BMW Approval	VW Approval
Mobil 1	0W-20 Advanced Fuel Economy	800	900	Fully synthetic formulation designed for enhanced fuel economy and cold weather performance.	Most vehicles that specify 0W-20 (newer Toyotas), 5W-20 and certain hybrids.	GF-4, SM	A1/B1-04	X	X	X			
Mobil 1	0W-30 Advanced Fuel Economy	800	900	Fully synthetic formulation designed for enhanced fuel economy and cold weather performance.	Most vehicles that specify 5W-30 or 10W-30. Corvette approved.	GF-4, SM	A1/B1-04	Corvette and Cadillac approved.	X	X			
Mobil 1	0W-40	1000	1100	Fully synthetic formulation designed to meet the requirements of many European vehicles.	Porsche. Many European vehicles. HT/TS applications. Viper approved.	SM	A3/B3-04, A3/B4-04			Dodge Viper approved	229.3/229.5	Longlife 01	502.00 /503.01/ 505.00
Mobil 1	5W-20	800	900	Fully synthetic formulation designed to meet the requirements of many newer vehicles including Hondas, Fords, Chryslers and newer Toyotas.	Vehicles that require 5W-20.	GF-4, SM	A1/B1-04	X	X	X			
Mobil 1	5W-30	800	900	Fully synthetic formulation designed to meet the requirements of many domestic, including GM, and imported vehicles.	Vehicles that require 5W-30. Corvette approved.	GF-4, SM	A1/B1-04, A5/B5-04	X	X	X			
Mobil 1	5W-50	1000	1100	Higher viscosity, fully synthetic formula designed for performance vehicles	Porsche. HT/HS applications.	SM	A3/B3-04, A3/B4-04				229.1 /229.3		505.00
Mobil 1	10W-30	800	900	Fully synthetic formula designed for domestics and imports	HT/HS applications. Racing and Flat tappet applications.	GF-4, SM	A1/B1-04, A5/B5-04	Corvette and Cadillac approved.		X			
Mobil 1	15W-50	1200	1300	Boosted, higher viscosity, fully synthetic formula designed for performance vehicles.	Trucks, SUVs and Vans that require 5W-30 and 10W-30.	SM	None						
Mobil 1 Truck & SUV	5W-30	800	900	Boosted, fully synthetic formula designed for gasoline powered Trucks, Vans and SUVs.	Most diesel applications. Applications requiring higher phosphorus (ZDDP), including engines with diesel particulate filters.	GF-4, SM	A1/B1-04, A5/B5-04	X	X	X			
Mobil 1 Turbo Diesel Truck	5W-40	1100	1200	Fully synthetic formula designed for diesel powered pick-ups and trucks.	Vehicles that require 5W-30 or 10W-30.	CJ-4, CI-4, CJ-4 Plus, SM, SL	E7-04/ E5-02						
Mobil 1 High Mileage	5W-30	900	1000	Boosted, fully synthetic formula designed for higher mileage vehicles.	Vehicles that require 5W-30 or 10W-30.	SL	A1/B1-04, A5/B5-04						
Mobil 1 High Mileage	10W-30	900	1000	Boosted, fully synthetic formula designed for higher mileage vehicles.	Higher viscosity applications.	SL	A3/B3-04, A3/B4-04						
Mobil 1 High Mileage	10W-40	900	1000	Boosted, fully synthetic formula designed for higher mileage vehicles.		SL	A3/B3-04, A3/B4-04						

MOST "SM" OILS ARE NOW BELOW 900 PARTS PER MILLION